

**APPLICATIONS AVAILABLE
INTERIOR WALL MOUNT,
OR FREE STANDING
SYSTEMS.**

FEATURES:

- Aluminum construction
- Attractive round formed arch
- Neoprene gaskets
- Safe touch-free drying
- Adjustable producers and layout
- TEFC motors - one year warranty
- Four producer system
- CNC built on holes

OPTIONS:

- 7.5 H.P., 10 H.P. or 15 H.P. producers
- Soft start panel
- Side producers
- UL listed starter panel
- Custom application
- Oscillating nozzle
- Thermo-plating (any color)




Made in the U.S.A.


premier
Touchless Drying System

STANDARD SERIES

STANDARD SERIES - S40



STANDARD SERIES - S40 - INTERIOR WALL MOUNT



VOLTAGE:

- 7.5 H.P.
 - 208 VAC FLA - 20.4
 - 230 VAC FLA - 18.4
 - 480 VAC FLA - 9.2
- 10 H.P.
 - 208 VAC FLA - 26.7
 - 230 VAC FLA - 23.8
 - 480 VAC FLA - 11.9
- 15 H.P.
 - 208 VAC FLA - 40.0
 - 230 VAC FLA - 35.0
 - 480 VAC FLA - 17.5